

INTENSIVE TAR REMOVER

Page: |

Compilation date: 03/12/2004

Revision date: 23/04/2015

Revision No: 9

Section 1: Identification of the substance/mixture and of the company/undertaking

I.I. Product identifier

Product name: INTENSIVE TAR REMOVER

Product code: *ITR/PB25/210114

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Solvent based cleaner for tar and adhesives.

1.3. Details of the supplier of the safety data sheet

Company name: AUTOGLYM

Works Road Letchworth Herts SG6 ILU

UK

Tel: +44 (0) 1462 677766

Fax: +44 (0) 1462 677712

Email: sds@autoglym.co.uk

I.4. Emergency telephone number

Emergency tel: +44 (0) 1462 489498 (24Hrs)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R10; Xn: R65; -: R66

Classification under CLP: STOT SE 3: H336; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315

Most important adverse effects: Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin

dryness or cracking.

2.2. Label elements

Label elements under CLP:

Hazard statements: * H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

INTENSIVE TAR REMOVER

Page: 2

Signal words: * Danger

Hazard pictograms: * GHS02: Flame

GHS07: Exclamation mark

GHS08: Health hazard







Precautionary statements: * P102: Keep out of reach of children.

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331: Do NOT induce vomiting.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P261: Avoid breathing vapours.

Label elements under CHIP:

Hazard symbols: Harmful.



Risk phrases: R10: Flammable.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S2: Keep out of the reach of children.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

INTENSIVE TAR REMOVER

Page: 3

NAPHTHA (PETROLEUM) HYDROTREATED HEAVY - REACH registered number(s): 01-2119463258-33-XXXX

	EINECS	CAS	CHIP Classification	CLP Classification	Percent		
919-857-5 -		-	Xn: R65; -: R10; -: R66	Asp. Tox. I: H304; STOT SE 3: H336;	70-90%		
				Flam. Liq. 3: H226; -: EUH066			
XYLENE							

215-535-7	1330-20-7	-: R10; Xn: R20/21; Xi: R38	Flam. Liq. 3: H226; Acute Tox. 4: H332;	1-10%
			Acute Tox. 4: H312; Skin Irrit. 2: H315	

3-BUTOXYPROPAN-2-OL - REACH registered number(s): 01-2119475527-28-****

225-878-4	5131-66-8	Xi: R36/38	Eye Irrit. 2: H319: Skin Irrit. 2: H315	1-10%
			,	

AMINE ALKYL BENZENE SULPHONATE

271-531-5	68584-24-7	Xn: R22; Xi: R38; Xi: R41	Acute Tox. 4: H302; Skin Irrit. 2: H315;	1-10%
			Eye Dam. I: H318	

Contains: >30% Aliphatic Hydrocarbons

5 - 15% Aromatic Hydrocarbons

<5% Anionic surfactants

Perfumes

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the

affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a

doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to

drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

INTENSIVE TAR REMOVER

Page: 4

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an

appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

Refer to section 13 of SDS for disposal considerations.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not

handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is

forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of

ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and

electrical equipment are not a source of ignition.

INTENSIVE TAR REMOVER

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED HEAVY

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1000 mg/m3	-	-	-

XYLENE

UK	220	441 mg/m3		
UK	220 mg/m3	441 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a

source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Nitrile gloves. Breakthrough time of the glove material > I hour.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Green-blue

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: No data available.

Solubility in water: Miscible

Viscosity: Non-viscous

Kinematic viscosity: -1.14

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3219)

Boiling point/range°C: 150 Melting point/range°C: No data available.

Flammability limits %: lower: No data available. upper: No data available.

Flash point°C: 38.6 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

INTENSIVE TAR REMOVER

Page: 6

Vapour pressure: No data available.

Relative density: 0.79 pH: Not applicable.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

II.I. Information on toxicological effects

Hazardous ingredients:

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

3-BUTOXYPROPAN-2-OL

ORL	RAT	LD50	5660	μl/kg
SKN	RBT	LD50	3100	mg/kg

Toxicity values: No data available.

INTENSIVE TAR REMOVER

Page: 7

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste code number: |40603

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

(NAPHTHA (PETROLEUM) HYDROTREATED HEAVY)

INTENSIVE TAR REMOVER

Page: 8

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: |||

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the

supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

R10: Flammable.

R20/21: Harmful by inhalation and in contact with skin.

R22: Harmful if swallowed.

R36/38: Irritating to eyes and skin.

R38: Irritating to skin.

INTENSIVE TAR REMOVER

Page: 9

R41: Risk of serious damage to eyes.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Legend to abbreviations: PNEC = predicted no effect level

DNEL = derived no effect level

LD50 = median lethal dose

LC50 = median lethal concentration

EC50 = median effective concentration

IC50 = median inhibitory concentration

dw = dry weight

bw = body weight

cc = closed cup

oc = open cup

MUS = mouse

GPG = guinea pig

RBT = rabbit

HAM = hamster

HMN = human

MAM = mammal

PGN = pigeon

IVN = intravenous

SCU = subcutaneous

SKN = skin

DRM = dermal

OCC = ocular/corneal

PCP = phycico-chemical properties

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.