

iQ500
LB88574 stainless steel
Canopy hood



The powerful canopy cooker hood is concealed above the cooktop.

- ✓ The 730 m³/h extraction rate supplies clean air when cooking.
- ✓ The energy-saving LED lighting ensures optimal visibility when cooking.
- ✓ The intensive setting temporarily increases the extraction rate when kitchen vapour is especially intense, with automatic revert after 6 min.

Features

Technical Data

Typology : Traditional
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 150
 Required niche size for installation (HxWxD) : 418mm x 836mm x 264mm
 Minimum distance above an electric hob : 500
 Minimum distance above a gas hob : 650
 Net weight (kg) : 10.411
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 630
 Boost position output recirculating (m³/h) : 310
 Maximum output recirculating air (m³/h) : 300
 Boost position air extraction (m³/h) : 730
 Number of lights : 2
 Noise level (dB) : 65
 Diameter of air outlet (mm) : 150 / 120
 Grease filter material : Washable aluminium
 EAN code : 4242003681534
 Connection Rating (W) : 277
 Current (A) : 3
 Voltage (V) : 220-240
 Frequency (Hz) : 50
 Plug type : Gardy plug w/ earthing
 Installation typology : Built-in



iQ500

LB88574 stainless steel

Canopy hood

Features

- Energy Efficiency Class: C (at a range of energy efficiency classes from A++ to E)
- Average Energy Consumption: 105.1 kWh/year
- Blower Efficiency Class: C*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: D
- Noise min./max. Normal Level: 52/65 dB

Variant:

Design:

Operating and power:

Environment and safety:

Comfort:

Measures:

- For installation in a kitchen cabinet
- Suitable for ducted or re-circulated extraction
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- RimVentilation
- Filter cover stainless steel
- Metal grease filter, dishwasher safe
- 2 x LED spot 1W
- Light Intensity: 266 lux
- Colour Temperature: 4000 K
- Electronic controls
- Push button controls with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- Twin channel high performance fan motor
- Extraction rate according to EN 61591 ø 15 cm:
 - max. Normal use 630 m³/h
 - Intensive 730 m³/h
- Noise level according to EN 60704-3 und EN 60704-2-13 exhaust air:
 - Max. normal use: 65 dB(A) re 1 pW sound pressure: 51 dB(A)
 - Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Max. extraction rate: 730 m³/h
- Dimensions (HxWxD): 418 x 860 x 300 mm
- built-in dimensions (HxWxD): 418 x 836 x 264 mm
- 120 or 150 mm diameter pipe
- Power rating: 277 W
- with one-way flap

* In accordance with the EU-Regulation No 65/2014

iQ500
LB88574 stainless steel
Canopy hood

Dimensioned drawings

