

Brolac Super Yacht Varnish

DESCRIPTION:	A premium quality varnish based on modified alkyd containing high-grade ingredients to provide a tough, durable and hardwearing clear finish. It has excellent flow and film build-up.
SCOPE:	Designed for use on interior and exterior timber where a clear gloss finish with good weather resistance is required. Provides good durability and weathering properties. Suitable for use within marine environments where a clear gloss finish is required.
COMPOSITION:	Alkyd Based, Lead Free
FINISH:	Glossy
COLOUR:	Clear
DRYING TIME:	Surface dry – 2 to 4 hours. Touch dry – 7 to 8 hours. Hard dry – 12 to 14 hours. Re-coatable – after 12 to 14 hours. Checked at 25 °C and relative humidity not more than 75%
SPECIFIC GRAVITY:	0.88 ± 0.02 Kgs/L
% VOLUME SOLIDS:	40 ± 2
SPREADING RATE:	12 - 14m ² / Litre (Depending on surface condition and its absorbency)
THINNER / CLEAN UP:	White Spirit. Clean the equipment immediately after use.
FLASH POINT:	37° C
PACK SIZE:	2.5 L, 1 Litre, 500ml, 250ml
APPLICATION:	Brush or Spray Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPARATION:

1.1 New Timber

Ensure that surface is dry, clean and well. Sand the surface with fine abrasive paper, dust off. Apply two coats of Brolac Super Yacht Varnish with an interval of 12-14 hours in between two coats. Thin, if necessary up to 20% by volume with White Spirit for ease of application.

1.2 Previously Varnished Timber in Fair Condition

Ensure that the surface is free from all traces of dirt, grease, and polish or wax. Touch up any bare areas with Brolac Super Yacht Varnish, thinned up to 20% with White Spirit.

1.3 Previously Varnished Timber in Poor Condition

Completely remove the old varnish with Paint Remover. Scrub off with clean water and stiff brush and allow to dry completely. Proceed as for new timber.

FINISHING:

Apply two or more coats of Brolac Super Yacht Varnish, allowing a minimum of 12 – 14 hours drying between coats. If necessary, rub down lightly between coats to remove any dust particles.

STORAGE:

Store in cool, dry condition away from sunlight

DISPOSAL:

Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

SHELF LIFE:

2 Years, when stored in original conditions.

NOTES:

- For maximum protection of exterior timber, apply three coats of Brolac Super Yacht Varnish.
- To prevent ingress of moisture to the end grain of exterior timber, these areas must be carefully sealed off with an adequate thickness of varnish. Do not apply to wet or damp timber.
- Do not use Brolac Super Yacht Varnish on floors.

SAFETY PRECAUTIONS:

Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.

FIRST AID:

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:
 The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
 HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06
 MALTA - EUROPE
 TEL: +356 2165 8855 / +356 2165 2996
 FAX: +356 2165 9409
 EMAIL: info@berger.com.mt
 WEBSITE: www.berger.com.mt