

25W Solar Flood light

Picture



Dimmension

Specification

Product Model	INS-SOL25W
Input Voltage	6V
Frequency Range	50Hz-60Hz
Power	25W
Lumen	CW 1700Lm
Material	Aluminium
Solar Board Type	Polysilicon
BatteryType	Lithium battery/lithium iron phosphate battery
Charging time	4—5 hours(optional)
Discharge time	8—12 hours(optional)
Color Temperature	CW 6000-6500K
Working Temperature	-30 — +60
Storage temperature	-30 — +60
Color Rendering Index	Ra>80
Lifespan	50,000h
Warranty	2 Years
IP Rating	Ip65
Recommend Instal height	3-5m
SMD Scoure Type	2835SMD
Working Model	intelligent control / Photosensitive control

Feature

SOLAR LIGHT:

Every evening, there is a light that automatically lights up for you to illuminate the yard, home the road, garage or deck, and automatically close at dawn. Built-in photoelectric sensor, Auto-on/Off Dusk to Dawn. 0 power consumption, no wiring required. Once installed, you don't need to worry about it.

Widely used in rural roads, residential roads, sidewalks, industrial parks, landscape lighting, scenic spots, parks, gardens, streets, squares, gardens, garages, lawns, passages, patios, sheds, farms, boats, camping, basketball courts, arenas, sports fields, etc.